



Our experience is the protection for your installation




SSK-type fuses: 10 years of highly efficient
transformer protection in electric circuits



*Our Protection.
Your Benefit.*


SIBA
Sicherungen | Fuses



© Yury Rumovsky – Fotolia

Experience counts. Transformer protection by SIBA – protection with tradition

- Switch-fuse combination: SIBA has been on board from the beginning.
- 10 years of SSK for special cases: SIBA identified early on that increasing transformer powers also call for new safeguarding concepts.
- Safety: SSK-type switch-fuse combinations with SIBA's SSK-type fuse-links limit the short-circuit power early in the process.
- SIBA's SSK-type transformer protection can even be comprehensively adapted to the requirements of installations of > 630 kVA: Detection of inadmissible heating caused by the installed temperature-limiting striker pin; provision of the optimum transfer current adjusted to the switch; consideration of the transformer's inrush currents as well as of the selectivity with regard to both superior and inferior protective elements. The coordination of the switching task between HV fuse-link and switch-disconnector is specified in IEC 62271-105.



Efficiency that saves costs: SSK-type fuses instead of circuit-breakers

- SIBA's SSK-type fuses in the switch-fuse combination can replace the more expensive circuit breakers, even in the case of transformer powers of up to 3,150 KVA.
- The specially developed electrical properties of SSK combinations meet the relevant requirements: Despite exhibiting a more quick-acting performance regarding the switch-opening time than standard fuses, the special SSK-type fuses maintain the minimum breaking current at lower power dissipation.
- For further information please visit our website: www.siba.de.



Energies with high standards Higher generator power, stronger transformers

- Specialist in the field of wind energy: Hardly any other industry demands so much of electrical installations as wind energy. A machine's medium installed active power of 1,720 kVA requires an apparent transformer power of up to 2,750 kVA – and the development continues. SIBA's SSK-type fuse-links have been further developed specially for this field of application and are currently designed for transformer powers of up to 3,150 kVA.
- Intensive research and development: One of the major challenges taken on by SIBA is the heating of fuses. Empirical work based on long-term test series involving the heating of fuses ensures that we are able to cope with this challenge and continue to further develop the SSK production series in order to meet the demands for regenerative energies in the future as well.



Bemessungsspannung Rated Voltage	Artikel Article	Bemessungsstrom Rated Current	Länge "e" Length "e"	Durchmesser D Diameter D
kV		A	mm	mm
6/12	30 012 43	63 - 100	292	67
	30 020 43	125		85
6/12	30 102 43	80 - 100	442	67
	30 103 43	125 - 160RC140		85
10/24	30 014 43	63 - 80	442	67
	30 022 43	100 - 140		85
20/36	30 024 43	63 - 80RC71	537	85

Bemessungsstrom Rated Current	Artikel Nr. Article No.	Bemessungs- ausschaltstrom Rated Breaking Current - I ₁	Minimaler Ausschaltstrom Min. Breaking Current - I ₃	Schmelzintegral Pre-Arcing- I ² t-Value	Ausschaltintegral Total I ² t-Value	Leistungsabgabe Power Loss
A		kA	A	A ² s	A ² s	W
63	30 012 43.63	63	210	9.300	74.000	62
80	30 012 43.80	63	280	12.800	103.000	76
100	30 012 43.100	63	320	22.300	138.000	98
125	30 020 43.125	63	450	39.000	323.000	135
80	30 102 43.80	63	280	12.800	103.000	72
100	30 102 43.100	63	320	22.300	138.000	93
125	30 103 43.125	63	450	39.000	323.000	128
160RC140 *	30 103 43.160	63	600	50.000	405.000	125
63	30 014 43.63	63	210	9.300	74.000	117
80	30 014 43.80	63	280	12.800	103.000	143
100	30 022 43.100	63	320	22.300	136.000	188
125	30 022 43.125	63	450	30.300	248.000	277
140RC100 *	30 022 43.140	63	500	55.000	395.000	116
63	30 024 43.63	40	280	9.300	74.000	189
80RC71 *	30 024 43.80	40	320	18.400	138.000	153

* Some SSK-type fuse-links have deviating designations, for example 160RC140. Here, the first value indicates the characteristic curve of the respective fuse-link, 160 A in this example. The letters "RC" (Rated Current) are followed by the rated current taking into consideration the maximum permissible heating of the fuse-link under standard conditions, 140 A in this example.

Hauptsitz / Head Office

SIBA GmbH

Borker Straße 20-22
D-44534 Lünen
Postfach 1940
D-44509 Lünen
Tel.: +49-2306-7001-0
Fax: +49-2306-7001-10
info@siba.de
www.siba.de

SIBA Unit Miniature Fuses

Tel.: +49-2306-7001-290
Fax: +49-2306-7001-99
elu@siba.de

Deutschland / Germany

SIBA Vertriebsbüro Freiberg

Untergasse 12
D-09599 Freiberg
Tel.: +49-3731-202283
Fax: +49-3731-202462
alexander.kolbe@siba.de

SIBA Vertriebsbüro Rhein/Ruhr

Espelweg 25
D-58730 Fröndenberg
Tel.: +49-2373-1753141
Fax: +49-2373-1753142
joerg.mattusch@siba.de

SIBA Vertriebsbüro Süd-West

Germersheimer Str. 101a
D-67360 Lingenfeld
Tel.: +49-6344-937510
Fax: +49-6344-937511
erwin.leuthner@siba.de

SIBA Vertriebsbüro Kassel

Sieberweg 20
34225 Baunatal
Tel.: +49-5601-965300
Fax: +49-5601-965301
achim.fischer@siba.de



International

SIBA Sicherungen- und Schalterbau Ges.m.b.H & Co. KG (Austria)

Ortsstraße 18 · A-2331 Vösendorf bei Wien
Tel.: +43-1-6994053 und 6992592
Fax: +43-1-699405316 und 699259216
info.siba@aon.at
www.siba-sicherungen.at

SIBA GmbH Beijing Rep. Office (China)

Room 207A, Building B, He Qiao Mansion No. 8
Guanghua Road, Chaoyang District,
Beijing 100026
Tel.: +86-10-65817776
Fax: +86-10-65812979
siba_china@sibafuse.cn
www.sibafuse.cn

SIBA Písek s.r.o. (Czech Rep.)

U Vodárny 1506 · 397 01 Písek
Tel.: +420-38-2265746
Fax: +420-38-2265746
sibacz@iol.cz · www.siba-pojistky.cz

SIBA Sikringer Danmark A/S (Denmark)

ehemals/former Ole Andersen A/S
Lunikvej 24 B · DK-2670 Greve
Tel.: +45-86828175 · Fax: +45-86814565
info@sikringer.dk · www.siba-sikringer.dk

SIBA Nederland B.V. (Netherlands)

Van Gentstraat 16
NL-5612 KM Eindhoven
Tel.: +31-40-2467071
Fax: +31-40-2439916
info@sibafuses.nl · www.siba-zekeringen.nl

SIBA Polska sp. z o.o. (Poland)

ul. Grzybowa 5G
05-092 Łomianki Dąbrowa Leśna
Tel.: +48-22-8321477
Fax: +48-22-8339118
siba@sibafuses.pl
www.siba-bezpieczniki.pl

„SIBA GmbH“ (Russia)

111 123, Moskva,
Shosse Entusiastov, 21 of. 407
Tel.: +7-495-9871413
Fax: +7-495-9871774
info@siba-predohraniteli.ru
www.siba-predohraniteli.ru

SIBA Fuses SA PTY. LTD. (South Africa)

P.O. Box 34261
Jeppestown 2043
Tel.: +27-11334-6560 / 4
Fax: +27-11334-7140
sibafuses@universe.co.za
www.siba-fuses.co.za

SIBA Far East Pte. LTD. (South East Asia)

24 Sin Ming Lane, # 07-105
Midview City
Singapore 573970
Republic of Singapore
Tel.: +65-62239225
Fax: +65-62341428
info@sibafuse.com.sg
www.sibafuse.com.sg

SIBA (UK) LTD. (United Kingdom)

19 Duke Street
Loughborough. Leics. LE11 1ED
Tel.: +44-1509-269719
Fax: +44-1509-236024
siba.uk@btconnect.com
www.siba-fuses.co.uk

SIBA Fuses LLC (United States of America)

29 Fairfield Place
West Caldwell, NJ 07006
Tel.: +1-973575-7422 (973-575-SIBA)
Fax: +1-973575-5858
info@sibafuses.com
www.siba-fuses.us

**Weitere Vertriebspartner weltweit /
Further distribution partners worldwide:**
www.siba.de / www.siba-fuses.com



Sicherungen | Fuses

*Our Protection.
Your Benefit.*